



# SEW151 PTFE coated


100% Polyester PTFe coated




White  
Weiss



2,0/2,2  
Decitex



0,56  
mm



0,09  
%



260  
gram



MD 512,4 N/5cm Length  
CD 518,3N/5cm cross

## FILTER MEDIA DATA

SEW 151 is a 100% PTFe coated spun bond filters media that is manufactured from continuous fibre which does not permit the particles to become embedded.

SEW 151 is very rugged and has a high burst strength that makes it resistant to abrasion, water, heat and chemicals.

100% Spun bond media makes pulse cleaning easier and is running with lower pressure drop. SEW 151 is a washable filter media.



Dry  
Trocken **120 Celsius**

Wet  
Feuchte **90 Celsius**

Air Permeability | 200Pa  
Luftdurchlässigkeit | 200Pa **410 m<sup>3</sup>/m<sup>2</sup>/hr**

## Chemical Resistance | Chemische Eigenschaften

	Excellent Sehr Gut	Good Gut	Fair Mässig
Oil/water resistance Öl und Wasserabweisend	X	X	X
Hydrolysis resistance Hydrolysebeständigkeit	X	X	X
Acid resistance Säurebeständigkeit	X	X	X
Alkaline resistance Alkalienbeständigkeit	X	X	X



Certificate No.  
201120318  
6210

Phone +45 5460 2080

S.E.W. North Filtration A/S \* Vesterbrogade 1, Section C \* DK-4930 Maribo  
E-mail: sales@northfiltration.com \* www.northfiltration.com \* VAT no.: DK 33 49 28 71