


SEW120


100% Polyester




White
Weiss



2,0/2,2
Decitex



0,58
mm



N/A
%



200
gram



MD 320 N/5cm Length
CD 300N/5cm cross

FILTER MEDIA DATA

SEW 120 is a 100% spun bond filters media that is manufactures from continuous fibre who does not permit the particles to become embedded.

SEW 120 is very rugged and have a high burst strength that make it resistant to abrasion water, heat and chemicals. 100 % Spun bond media makes pulse cleaning easier and are running with lower pressure drop SEW 120 is a washable filter media.



Dry
Trocken

120 Celsius

Wet
Feuchte

90 Celsius

Air Permeability | 200Pa
Luftdurchlässigkeit | 200Pa

800 m3/m2/hr

Chemical Resistance | Chemische Eigenschaften

	Excellent Sehr Gur	Good Gut	Fair Mässig
Oil/water resistance Öl und Wasserabweisend	X	X	X
Hydrolysis resistance Hydrolysebeständigkeit	X	X	X
Acid resistance Säurebeständigkeit	X	X	X
Alkaline resistance Alkalienbeständigkeit	X	X	X



Phone +45 5460 2080

S.E.W. North Filtration A/S * Vesterbrogade1, Section C * DK-4930 Maribo
E-mail: sales@northfiltration.com * www.northfiltration.com * VAT no.: DK 33 49 28 71